

Matt Emulsion Exterior Paint

Zydex[®]
Innovating for Sustainability



CERTIFIED



Matt Emulsion

Matt Emulsion is a premium exterior paint with a rich matt finish. It's inherent deep matt effect and carefully selected pigments provide unsurpassed color depth and brilliancy even in the most difficult lighting conditions. Matt Emulsion's ability to hide surface defects leads to an even and consistent finish even at sharp angles. The paint is extremely resistant to burnishing and mechanical abrasion making it suitable for even the most demanding high traffic interior spaces. Being highly breathable, it is extremely resistant to peel-off and blistering. Designed for excellent dirt release, it is easily washable and highly scrub resistant. Available in a wide range of colours.

FEATURES

- ☒ Rich Matt Finish
- ☒ Low Odour, Low VOC
- ☒ Breathable
- ☒ Excellent Burnish Resistance
- ☒ Anti-Fungal
- ☒ Bright Colours
- ☒ Washable
- ☒ Wide Range of Colours

Toll Free:
1-800-12300-7666

www.zydexgroup.com

Matt Emulsion

MATT EMULSION APPLICATION GUIDELINE

Substrate Preparation

All loose, flaking and unstable material must be identified and then thoroughly removed. All surfaces must be thoroughly washed down with clean cold water using a pressure washer to remove all surface dirt and dust. All surface defects and cracks must be repaired using Zydex recommended compounds only. When all surfaces are clean, dry, dust free and free from all surface contaminants, painting may proceed. For repainting, surface preparation must be done in accordance with procedure laid down by the Zydex representative or authorised partner.

Application

Matt Emulsion must be applied as two coat system. Both coats can be diluted between 30-40 percent using Potable Water depending on surface. The second coat is to be applied with a minimum gap of 12 hours between coats. Cover all surfaces which are not to be painted, in particular those that are mineral in nature such as glass, stone, ceramics etc.

Consumption

Approximately 4.6 m² /ltr (50 sq.ft. /ltr) for 2 coats.

Consumption guideline is quoted for smooth surfaces with normal absorbency. Actual consumption may vary based on surface characteristics and is the responsibility of the applicator.

Cleaning of Equipment

Clean immediately with water after use.

Packaging and Storage

1 ltr, 4 ltr and 20 ltr.

Shelf life approximately 48 months in a cool shaded area. All unused paint must be packed in smaller air-tight containers to maintain minimum air volume.

Specifications

Density: 1.20 - 1.50 g/cm³

Gloss at 85°: < 2

pH: Approximate 10.5

Version No. VN01/29/2024