

# Matt Emulsion Interior Paint

**Zydex**<sup>®</sup>  
Innovating for Sustainability



**CERTIFIED**



## Matt Emulsion

Matt Emulsion is a premium interior paint with a rich matt finish. It's inherent deep matt effect and carefully selected pigments provide unsurpassed color depth and brilliancy even in the most difficult lighting conditions. Matt Emulsion's ability to hide surface defects leads to an even and consistent finish even at sharp angles. The paint is extremely resistant to burnishing and mechanical abrasion making it suitable for even the most demanding high traffic interior spaces. Being highly breathable, it is extremely resistant to peel-off and blistering. Designed for excellent dirt release, it is easily washable and highly scrub resistant. Available in a white and pastel tones.

## FEATURES

- Rich Matt Finish
- Low Odour, Low VOC
- Breathable
- Excellent Burnish Resistance
- Anti-Fungal
- Bright Colours
- Washable
- White and Pastel Tones

Toll Free:  
**1-800-12300-7666**

[www.zydexgroup.com](http://www.zydexgroup.com)

# Matt Emulsion

## MATT EMULSION APPLICATION GUIDELINE

### Substrate Preparation

The substrate must be sound, solid, dry, clean and free of dust and grease. Substrate and air temperature during application and drying > 5°C. Matt Emulsion must be applied using either brush or roller suitable for interior painting. In case of re-painting, the adhesion of the old paint must be checked using cross-hatch method. If paint is found to be non-adherent, it must be removed completely and surface must be re-prepared. In case of adherent surfaces, sand down the existing paint to roughen the surface and clean in to ensure it is free of debris. All defects and cracks should be filled using suitable repair compound. Painting with Matt Emulsion may now proceed. Matt Emulsion is not suitable for painting over metal, wood, varnishes and oil based paints.

### Application

Matt Emulsion must be applied in principle as a two coat system diluted with water up to 30 percent. In case of patchy or inhomogeneous surfaces a coat of Zydex Premium Wall Primer may be required. A minimum gap of 4 hours must be observed between subsequent coats. Cover all surfaces which are not to be painted. Please ensure that at no point is Matt Emulsion diluted beyond 30 percent as this may severely affect the end film properties.

### Consumption

Approximately 7.5 m<sup>2</sup> /ltr (80 sq.ft./ltr) for 2 coats.

Consumption guideline is quoted for smooth surfaces with normal absorbency. Actual consumption may vary based on surface characteristics and is the responsibility of the applicator.

### Cleaning of Equipment

Clean immediately with water after use.

### Packaging and Storage

1 ltr, 4 ltr and 20 ltr.

Shelf life approximately 48 months in a cool shaded area. All unused paint must be packed in smaller air-tight containers to maintain minimum air volume.

### Specifications

Density: 1.20 - 1.50 g/cm<sup>3</sup>

Gloss at 85°: < 2

Flash Point: NA

Version No. VN01/29/2024